

View Online at <https://aerobasegroup.com/nsn/5950-00-337-9563>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.688 inches single mounting facility single center group1.688 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.438 inches single mounting facility single center group1.438 inches single mounting facility single center group

**Frequency Rating:**

320.0 hertz single component and 320.0 hertz single component and 1.76 kilohertz single component1.76 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

**Body Length:**

2.313 inches 2.313 inches

**Body Width:**

2.063 inches 2.063 inches

**Body Height:**

2.500 inches 2.500 inches

**Inclosure Type:**

Openopen

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Voltage:**

6.30 ac volts single component 3rd secondary and 13.50 ac volts single component 3rd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A058b0