

View Online at <https://aerobasegroup.com/nsn/5950-00-345-7472>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.040 inches single mounting facility single center group and 5.080 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.860 inches single mounting facility single center group and 1.900 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.000 inches

Body Width:

2.730 inches

Body Height:

3.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

3.0 amperes ac single component 1st secondary

Winding Power Rating:

6.52 volts-amperes single component 2nd secondary99.0 volts-amperes single component single primary6.52 volts-amperes single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary6.30 ac volts single component 2nd secondary115.00 ac volts single component single primary and 120.00 ac volts single component single primary and 125.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

9 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0