

View Online at <https://aerobasegroup.com/nsn/5950-00-348-0420>

**Reliability Indicator:**

Not established

**Inductance Rating:**

60.00 microhenries single component single primary

**Frequency Rating:**

1.0 kilohertz single component

**Primary To Secondary Turn Ratio:**

1 to 1-1/3 single component

**Pulse Repetition Rate:**

320.0 hertz single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

1.781 inches

**Body Width:**

1.656 inches

**Body Height:**

3.125 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Distance Between Mounting Facility Centers:**

1.687 inches single mounting facility single center group

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.138 inches single group

**Dc Resistance Rating In Ohms:**

250.000 single component single primary

**Special Features:**

Secondary winding also has 600.00hms

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

5 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0