## NSN 5950-00-348-0420

Pulse Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-348-0420
Reliability Indicator:
Not established
Inductance Rating:
60.00 microhenries single component single primary
Frequency Rating:
1.0 kilohertz single component
Primary To Secondary Turn Ratio:
1 to 1-1/3 single component
Pulse Repetition Rate:
320.0 hertz single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
1.781 inches
Body Width:
1.656 inches
Body Height:
3.125 inches
Maximum Operating Temp:
105.0 degrees celsius
Distance Between Mounting Facility Centers:
1.687 inches single mounting facility single center group
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thread Size:
0.138 inches single group
Dc Resistance Rating In Ohms:
250.000 single component single primary
Special Features:
Secondary winding also has 600.00hms
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
5 turret
Shelf Life:

N/a

## NSN 5950-00-348-0420

Pulse Transformer - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A058b0