

View Online at <https://aerobasegroup.com/nsn/5950-00-348-2796>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

1.938 inches

Body Width:

1.812 inches

Body Height:

2.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

400.0 milliamperes ac single component 3rd secondary and 400.0 milliamperes ac single component 3rd secondary and 100.0 milliamperes ac single component 3rd secondary and 100.0 milliamperes ac single component 3rd secondary and 100.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

90.00 ac volts single component 2nd secondary 90.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0