# NSN 5950-00-348-3799

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-348-3799

## **Reliability Indicator:**

Not establishednot established

#### **Frequency Rating:**

400.0 hertz single component400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### Body Length:

0.970 inches 0.970 inches

#### **Body Outside Diameter:**

2.600 inches 2.600 inches

#### Maximum Operating Temp:

100.0 degrees celsius100.0 degrees celsius

#### Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

1 single group1 single group

#### Mounting Method:

Threaded hole single groupthreaded hole single group

## Winding Function And Quantity:

1 primary single component and 1 primary single component and 7 secondary single component7 secondary single component

#### Thread Size:

0.138 inches single group0.138 inches single group

#### Winding Operating Current:

625.0 milliamperes ac single component 3rd secondary

# Winding Operating Voltage:

34.50 ac volts single component 3rd secondary115.00 ac volts single component single primary115.00 ac volts single component single primary23.50 ac volts single component 4th secondary

#### **Special Features:**

1primary winding; 7secondary windings; number 7 having a center tap1primary winding; 7secondary windings; number 7 having a center tap

#### Thread Series Designator:

Unc single group

#### Terminal Type And Quantity:

17 solder stud

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# Fiig:

A058b0