NSN 5950-00-349-6351

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/psp/5050-00-340-6351

| View Online at https://aerobasegroup.com/nsn/5950-00-349-6351 |
|--|
| Reliability Indicator: |
| Not establishednot established |
| Frequency Rating: |
| 800.0 hertz single component800.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single componentsingle phase to single phase single component |
| Body Length: |
| 1.500 inches 1.500 inches |
| Body Width: |
| 0.750 inches 0.750 inches |
| Body Height: |
| 0.365 inches 0.365 inches |
| Maximum Operating Temp: |
| 130.0 degrees celsius130.0 degrees celsius |
| Distance Between Mounting Facility Centers: |
| 0.750 inches single mounting facility single center group0.750 inches single mounting facility single center group |
| Inclosure Type: |
| Fully enclosedfully enclosed |
| Mounting Facility Quantity: |
| 2 single group2 single group |
| Mounting Method: |
| Threaded hole single groupthreaded hole single group |
| Winding Function And Quantity: |
| 2 primary single component and 2 primary single component and 2 secondary single component2 secondary single component |
| Thread Size: |
| 0.086 inches single group |
| Winding Operating Voltage: |
| 5.97 ac volts single component 1st secondary1.00 ac volts single component all primary6.92 ac volts single component 2nd secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 8 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No Fiig:

A058b0