NSN 5950-00-349-6352

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-349-6352

_			
R۵	liahi	litv	Indicator:
ĸe	IIabi	IILV	mulcator.

Not establishednot established

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

1.500 inches 1.500 inches

Body Width:

0.750 inches 0.750 inches

Body Height:

0.625 inches 0.625 inches

Maximum Operating Temp:

130.0 degrees celsius 130.0 degrees celsius

Distance Between Mounting Facility Centers:

0.750 inches single mounting facility single center group0.750 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 1 secondary single component1 secondary single component

Thread Size:

0.086 inches single group 0.086 inches single group

Winding Operating Voltage:

10.40 ac volts single component single secondary and 10.40 ac volts single component single secondary and 12.00 ac volts single component single secondary and 22.40 ac volts single component single secondary 22.40 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0