

View Online at <https://aerobasegroup.com/nsn/5950-00-351-5049>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.750 inches

Body Width:

3.000 inches

Body Height:

3.500 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Voltage:

3.00 ac volts single component single secondary and 110.00 ac volts single component single primary and 120.00 ac volts single component single primary
5.00 ac volts single component single secondary and 8.00 ac volts single component single secondary and 11.00 ac volts single component single secondary
and 70.00 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0