

View Online at <https://aerobasegroup.com/nsn/5950-00-351-6437>

**Reliability Indicator:**

Not establishednot establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches single mounting facility single center group0.875 inches single mounting facility single center group0.875 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.125 inches single mounting facility single center group1.125 inches single mounting facility single center group1.125 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.157 inches single group0.157 inches single group0.157 inches single group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

**Body Length:**

2.125 inches 2.125 inches 2.125 inches

**Body Width:**

1.625 inches 1.625 inches 1.625 inches

**Body Height:**

2.062 inches 2.062 inches 2.062 inches

**Maximum Operating Temp:**

130.0 degrees celsius130.0 degrees celsius130.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and flange single group and unthreaded hole single groupunthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

**Winding Operating Current:**

2.0 amperes ac single component single secondary

**Winding Power Rating:**

15.0 volts-amperes single component single secondary

**Winding Operating Voltage:**

115.00 ac volts single component single primary6.30 ac volts single component single secondary115.00 ac volts single component single primary

**Terminal Type And Quantity:**

5 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

**Fig:**

A058b0