

View Online at <https://aerobasegroup.com/nsn/5950-00-351-6437>

Reliability Indicator:

Not establishednot establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches single mounting facility single center group0.875 inches single mounting facility single center group0.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.125 inches single mounting facility single center group1.125 inches single mounting facility single center group1.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.157 inches single group0.157 inches single group0.157 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Body Length:

2.125 inches 2.125 inches 2.125 inches

Body Width:

1.625 inches 1.625 inches 1.625 inches

Body Height:

2.062 inches 2.062 inches 2.062 inches

Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius130.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Flange single group and flange single group and flange single group and unthreaded hole single groupunthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Power Rating:

15.0 volts-amperes single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary6.30 ac volts single component single secondary115.00 ac volts single component single primary

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

Fig:

A058b0