

View Online at <https://aerobasegroup.com/nsn/5950-00-355-9946>

Reliability Indicator:

Not established

Overall Length:

4.688 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.719 inches single mounting facility single center group and 3.781 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.969 inches single mounting facility single center group and 3.031 inches single mounting facility single center group

Overall Width:

3.813 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

145.0 volt-ampere single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

600.0 milliamperes ac single component 3rd secondary

Winding Power Rating:

42.8 volts-amperes single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary 19.00 dc volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0