

View Online at <https://aerobasegroup.com/nsn/5950-00-355-9946>

**Reliability Indicator:**

Not established

**Overall Length:**

4.688 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.719 inches single mounting facility single center group and 3.781 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.969 inches single mounting facility single center group and 3.031 inches single mounting facility single center group

**Overall Width:**

3.813 inches

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

145.0 volt-ampere single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

2 primary single component and 3 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

600.0 milliamperes ac single component 3rd secondary

**Winding Power Rating:**

42.8 volts-amperes single component 1st secondary

**Winding Operating Voltage:**

6.30 ac volts single component 3rd secondary 19.00 dc volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0