

View Online at <https://aerobasegroup.com/nsn/5950-00-365-9940>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.500 inches

Body Width:

3.750 inches

Body Height:

3.250 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Voltage:

18.90 ac volts single component 3rd secondary239.00 ac volts single component 4th secondary100.00 ac volts single component all primary and 115.00 ac volts single component all primary and 120.00 ac volts single component all primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

19 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0