NSN 5950-00-366-0041

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-366-0041

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility single center group

Frequency Rating:

48.0 hertz single component and 450.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 2.500 inches and 2.625 inches

Body Width:

Between 2.125 inches and 2.250 inches

Body Height:

Between 4.375 inches and 4.500 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Voltage:

36.50 ac volts single component 2nd secondary6.30 ac volts single component 3rd secondary103.50 ac volts single component single primary and 109.25 ac volts single component single primary and 115.00 ac volts single component single primary and 120.75 ac volts single component single primary and 126.50 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5950-00-366-0041

Power Transformer - Page 2 of 2



Fiig:

A058b0