

View Online at <https://aerobasegroup.com/nsn/5950-00-369-6972>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.750 inches single mounting facility single center group0.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.750 inches single mounting facility single center group0.750 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

1.125 inches 1.125 inches

**Body Width:**

1.312 inches 1.312 inches

**Body Height:**

1.125 inches 1.125 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Thready Qty Per Inch (tpi):**

40 single group40 single group

**Thread Size:**

0.112 inches single group0.112 inches single group

**Winding Power Rating:**

2.0 watts single component all secondary

**Winding Operating Voltage:**

5.00 ac volts single component 2nd secondary and 14.00 ac volts single component 2nd secondary and 19.00 ac volts single component  
2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

14 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0