

View Online at <https://aerobasegroup.com/nsn/5950-00-369-9498>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Frequency Rating:

48.0 hertz single component and 48.0 hertz single component and 450.0 hertz single component450.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

3.438 inches 3.438 inches

Body Width:

2.760 inches 2.760 inches

Body Height:

4.500 inches 4.500 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Voltage:

37.50 ac volts single component 3rd secondary6.30 ac volts single component 4th secondary103.50 ac volts single component single primary and 109.25 ac volts single component single primary and 115.00 ac volts single component single primary and 120.75 ac volts single component single primary and 126.50 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0