

View Online at <https://aerobasegroup.com/nsn/5950-00-370-2621>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.880 inches

Body Width:

3.510 inches

Body Height:

4.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

660.0 milliamperes ac single component 1st secondary

Winding Power Rating:

7.9 volts-amperes single component 3rd secondary

Winding Operating Voltage:

79.00 ac volts single component 3rd secondary

Special Features:

Terminals on top of case

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0