

View Online at <https://aerobasegroup.com/nsn/5950-00-371-9157>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.125 inches single group

Frequency Rating:

25.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

7.188 inches

Body Width:

5.625 inches

Body Height:

4.750 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Voltage:

73.30 ac volts single component single primary and 88.00 ac volts single component single primary and 95.00 ac volts single component single primary and 105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 190.00 ac volts single component single primary or 210.00 ac volts single component single primary and 230.00 ac volts single component single primary or 250.00 ac volts single component single primary

Terminal Type And Quantity:

19 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0