

View Online at <https://aerobasegroup.com/nsn/5950-00-372-2238>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.360 inches single mounting facility single center group and 1.390 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.235 inches single mounting facility single center group and 1.265 inches single mounting facility single center group

**Frequency Rating:**

380.0 hertz single component and 400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core and brought out to terminal single component

**Body Length:**

Between 1.812 inches and 1.937 inches

**Body Width:**

Between 1.687 inches and 1.812 inches

**Body Height:**

Between 2.563 inches and 2.750 inches

**Maximum Operating Temp:**

65.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

265.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

24.00 ac volts single component single secondary 115.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0