

View Online at <https://aerobasegroup.com/nsn/5950-00-372-2238>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.360 inches single mounting facility single center group and 1.390 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.235 inches single mounting facility single center group and 1.265 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

Between 1.812 inches and 1.937 inches

Body Width:

Between 1.687 inches and 1.812 inches

Body Height:

Between 2.563 inches and 2.750 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

265.0 milliamperes ac single component single secondary

Winding Operating Voltage:

24.00 ac volts single component single secondary 115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0