

View Online at <https://aerobasegroup.com/nsn/5950-00-376-9596>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.375 inches single mounting facility single center group2.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.250 inches single mounting facility single center group3.250 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 50.0 hertz single component and 1.0 kilohertz single component1.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and brought out to terminal single componentinternal shield grounded to inclosure and brought out to terminal single component

**Body Length:**

3.000 inches 3.000 inches

**Body Width:**

2.469 inches 2.469 inches

**Body Height:**

2.844 inches 2.844 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary115.00 ac volts single component single primary6.30 ac volts single component 3rd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

12 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0