NSN 5950-00-378-0325

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-378-0325

Reliability Indicator:

Not establishednot established

Overall Length:

Between 1.719 inches and 1.719 inches and 1.719 inches and 1.812 inches 1.812 inches 1.812 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.234 inches single mounting facility single center group and 1.234 inches single mounting facility single center group and 1.234 inches single mounting facility single center group 1.266 inches single mounting facility single center group 1.266 inches single mounting facility single center group 1.266 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.046 inches single mounting facility single center group and 1.046 inches single mounting facility single center group and 1.046 inches single mounting facility single center group 1.078 inches single mounting facility single center group 1.078 inches single mounting facility single center group 1.078 inches single mounting facility single center group

Overall Height:

Between 2.688 inches and 2.688 inches and 2.688 inches and 2.812 inches 2.812 inches

Overall Width:

Between 1.469 inches and 1.469 inches and 1.469 inches and 1.531 inches 1.531 inches

Frequency Rating:

60.0 hertz single component60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component component

Maximum Transformer Power Rating:

5.0 volt-ampere single component5.0 volt-ampere single component5.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single componentinternal shield grounded to core single component

Maximum Operating Temp:

130.0 degrees celsius 130.0 degrees celsius 130.0 degrees celsius

Inclosure Type:

Hermetically sealedhermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thread Size:

0.138 inches single group0.138 inches single group0.138 inches single group

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary5.00 ac volts single component single secondary115.00 ac volts single component single primary

Thread Series Designator:

NSN 5950-00-378-0325

Power Transformer - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0