

View Online at <https://aerobasegroup.com/nsn/5950-00-385-8906>

Reliability Indicator:

Not establishednot establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility all center groupings5.000 inches single mounting facility all center groupings5.000 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility all center groupings4.000 inches single mounting facility all center groupings4.000 inches single mounting facility all center groupings

Frequency Rating:

47.0 hertz single component and 47.0 hertz single component and 47.0 hertz single component and 63.0 hertz single component63.0 hertz single component63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

Between 5.880 inches and 5.880 inches and 5.880 inches and 6.000 inches 6.000 inches 6.000 inches

Body Width:

Between 4.880 inches and 4.880 inches and 4.880 inches and 5.000 inches 5.000 inches 5.000 inches

Body Height:

Between 4.880 inches and 4.880 inches and 4.880 inches and 5.000 inches 5.000 inches 5.000 inches

Inclosure Type:

Fully enclosedfully enclosedfully enclosed

Mounting Facility Quantity:

8 all groupings8 all groupings8 all groupings

Mounting Method:

Threaded hole all groupingsthreaded hole all groupingsthreaded hole all groupings

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 6 secondary single component6 secondary single component6 secondary single component

Thread Size:

0.250 inches all groupings0.250 inches all groupings

Winding Operating Current:

3.0 amperes dc single component 2nd secondary and 8.0 amperes dc single component 2nd secondary

Winding Operating Voltage:

9.70 ac volts single component 4th secondary48.50 ac volts single component 1st secondary

Special Features:

All voltages are stated as open circuit; all currents are stated as rectified; 1 primary, 6 secondary windings; secondaries 5 & 6 are rated 115vrms

Thread Series Designator:

Unf all groupings

Terminal Type And Quantity:

20 threaded stud

Demilitarization:

No

Fig:

A058b0