

View Online at <https://aerobasegroup.com/nsn/5950-00-386-8903>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

**Mounting Slot Width:**

0.200 inches single group0.200 inches single group

**Frequency Rating:**

50.0 hertz single component and 50.0 hertz single component and 400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

3.030 inches 3.030 inches

**Body Width:**

3.030 inches 3.030 inches

**Body Height:**

2.530 inches 2.530 inches

**Inclosure Type:**

Partially enclosed, double shellpartially enclosed, double shell

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and slot single groupslot single group

**Winding Function And Quantity:**

2 primary single component and 2 primary single component and 1 secondary single component1 secondary single component

**Winding Operating Current:**

1.6 amperes ac single component single secondary

**Winding Operating Voltage:**

48.00 ac volts single component single secondary

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0