

View Online at <https://aerobasegroup.com/nsn/5950-00-386-8903>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

Mounting Slot Width:

0.200 inches single group0.200 inches single group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

3.030 inches 3.030 inches

Body Width:

3.030 inches 3.030 inches

Body Height:

2.530 inches 2.530 inches

Inclosure Type:

Partially enclosed, double shellpartially enclosed, double shell

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and slot single groupslot single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 1 secondary single component1 secondary single component

Winding Operating Current:

1.6 amperes ac single component single secondary

Winding Operating Voltage:

48.00 ac volts single component single secondary

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0