

View Online at <https://aerobasegroup.com/nsn/5950-00-389-7139>

Reliability Indicator:

Not established

Overall Height:

3.260 inches

Overall Width:

5.012 inches

Mounting Hole Diameter:

0.219 inches single group

Frequency Rating:

47.0 hertz single component and 410.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.850 inches

Body Width:

3.200 inches

Body Height:

3.000 inches

End Application:

Ticonderoga class cg (47), tarawa class lha, wasp class lhd, spruance class dd (963), oliver perry class ffg, emory s. Land class as, forrestal class cv, nimitz class cvn, supply class aoe

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

500.0 milliamperes ac single component 3rd secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

4.25 ac pounds per hour wet single component 4th secondary and 8.50 ac pounds per hour wet single component 4th secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0