

NSN 5950-00-393-8184 Power Transformer - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5950-00-393-8184 **Reliability Indicator:** Not established **Overall Length:** 3.300 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.750 inches single mounting facility single center group **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.750 inches single mounting facility single center group **Overall Height:** 2.260 inches **Overall Width:** 2.325 inches **Mounting Hole Diameter:** 0.126 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye and wye-delta

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 8 secondary single component

Winding Operating Current:

700.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

46.00 ac pounds per hour wet single component 2nd secondary

Terminal Type And Quantity:

28 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5950-00-393-8184

Power Transformer - Page 2 of 2



Fiig:

A058b0