

NSN 5950-00-393-8184 Power Transformer - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5950-00-393-8184 **Reliability Indicator:** Not established **Overall Length:** 3.300 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.750 inches single mounting facility single center group **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.750 inches single mounting facility single center group **Overall Height:** 2.260 inches **Overall Width:** 2.325 inches **Mounting Hole Diameter:** 0.126 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship:

Three phase to three phase single component

**Transformer Winding Connection Type:** 

Wye-wye and wye-delta

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

**Inclosure Type:** 

Open

**Mounting Facility Quantity:** 

4 single group

**Mounting Method:** 

Flange single group and unthreaded hole single group

**Winding Function And Quantity:** 

1 primary single component and 8 secondary single component

**Winding Operating Current:** 

700.0 milliamperes ac single component 4th secondary

**Winding Operating Voltage:** 

46.00 ac pounds per hour wet single component 2nd secondary

**Terminal Type And Quantity:** 

28 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

## NSN 5950-00-393-8184

Power Transformer - Page 2 of 2



Fiig:

A058b0