

View Online at <https://aerobasegroup.com/nsn/5950-00-394-0289>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

3.562 inches 3.562 inches

Body Width:

3.062 inches 3.062 inches

Body Height:

4.875 inches 4.875 inches

Maximum Operating Temp:

80.0 degrees celsius80.0 degrees celsius

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

320.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

33.00 ac volts single component 1st secondary26.00 ac volts single component 3rd secondary26.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0