

View Online at <https://aerobasegroup.com/nsn/5950-00-399-7495>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.313 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.188 inches single mounting facility single center group

Mounting Hole Diameter:

0.125 inches single group

Frequency Rating:

350.0 hertz single component and 450.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

5.000 inches

Body Width:

3.875 inches

Body Height:

5.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

35.0 milliamperes ac single component single secondary

Winding Operating Voltage:

3.00 ac kilovolts single component single secondary and 3.15 ac kilovolts single component single secondary and 3.30 ac kilovolts single component single secondary and 3.45 ac kilovolts single component single secondary

Terminal Type And Quantity:

5 tab, solder lug and 2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0