

View Online at <https://aerobasegroup.com/nsn/5950-00-401-6442>

Reliability Indicator:

Not establishednot established

Overall Height:

0.755 inches 0.755 inches

Mounting Hole Diameter:

0.116 inches single group and 0.116 inches single group and 0.124 inches single group0.124 inches single group

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

Between 0.868 inches and 0.868 inches and 0.870 inches 0.870 inches

Body Width:

Between 0.718 inches and 0.718 inches and 0.780 inches 0.780 inches

Body Height:

Between 0.615 inches and 0.615 inches and 0.740 inches 0.740 inches

Maximum Operating Temp:

165.0 degrees celsius165.0 degrees celsius

Distance Between Mounting Facility Centers:

0.800 inches single mounting facility single center group and 0.800 inches single mounting facility single center group and 0.832 inches single mounting facility single center group0.832 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0