

View Online at <https://aerobasegroup.com/nsn/5950-00-401-6457>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.500 inches single mounting facility single center group1.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.500 inches single mounting facility single center group1.500 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single componentinternal shield grounded to core single component

**Body Length:**

2.000 inches 2.000 inches

**Body Width:**

2.000 inches 2.000 inches

**Body Height:**

1.688 inches 1.688 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

1.0 amperes ac single component 1st secondary

**Winding Operating Voltage:**

26.00 ac volts single component single primary and 115.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0