

View Online at <https://aerobasegroup.com/nsn/5950-00-402-9025>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.688 inches single mounting facility single center group2.688 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.312 inches single mounting facility single center group3.312 inches single mounting facility single center group

**Overall Height:**

6.062 inches 6.062 inches

**Frequency Rating:**

57.0 hertz single component and 57.0 hertz single component and 63.0 hertz single component63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

**Body Length:**

4.312 inches 4.312 inches

**Body Width:**

3.688 inches 3.688 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

**Thread Size:**

0.190 inches single group0.190 inches single group

**Winding Operating Current:**

1.0 amperes ac single component 3rd secondary

**Winding Operating Voltage:**

6.30 ac volts single component 1st secondary325.00 ac volts single component 4th secondary10.00 ac volts single component 3rd secondary1700.00 ac volts single component 2nd secondary

**Special Features:**

1primary winding; 5secondary windings

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0