

View Online at <https://aerobasegroup.com/nsn/5950-00-402-9025>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.688 inches single mounting facility single center group2.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.312 inches single mounting facility single center group3.312 inches single mounting facility single center group

Overall Height:

6.062 inches 6.062 inches

Frequency Rating:

57.0 hertz single component and 57.0 hertz single component and 63.0 hertz single component63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

4.312 inches 4.312 inches

Body Width:

3.688 inches 3.688 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

1.0 amperes ac single component 3rd secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary325.00 ac volts single component 4th secondary10.00 ac volts single component 3rd secondary1700.00 ac volts single component 2nd secondary

Special Features:

1primary winding; 5secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0