Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-403-2415

| Deliebility Indianton |
|---|
| Reliability Indicator: |
| Not established |
| Overall Height: |
| 2.000 inches |
| Impedance Rating In Ohms: |
| 600.0 single component single secondary |
| Frequency Rating: |
| 300.0 hertz single component and 1.8 kilohertz single component |
| Maximum Transformer Power Rating: |
| 22.0 decibels single component |
| Primary To Secondary Turn Ratio: |
| 1 to 1 single component |
| Winding Shielding Method: |
| Internal shield brought out to terminal single component |
| Body Length: |
| Between 1.250 inches and 1.312 inches |
| Body Width: |
| Between 1.250 inches and 1.312 inches |
| Body Height: |
| Between 1.625 inches and 1.750 inches |
| Distance Between Mounting Facility Centers: |
| 1.250 inches single mounting facility single center group |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 40.0 milliamperes dc single component single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 5 wire hook |
| Shelf Life: |
| N/a |
| 1 W G |

Audio Frequency Transformer - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0