## NSN 5950-00-403-3975

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-403-3975

eliability Indicator:
ot established
enter To Center Distance Between Mounting Facilities Parallel To Lengt
.690 inches single mounting facility single center group
enter To Center Distance Between Mounting Facilities Parallel To Width
.000 inches single mounting facility single center group
requency Rating:
0.0 hertz single component and 60.0 hertz single component
nput-output Phase Relationship:
ingle phase to single phase single component
/inding Shielding Method:
nternal shield grounded to inclosure single component
ody Length:
.940 inches
ody Width:
.650 inches
ody Height:
.310 inches
nclosure Type:
ermetically sealed
Iounting Facility Quantity:
single group
Iounting Method:
hreaded stud single group
/inding Function And Quantity:
primary single component and 2 secondary single component
hready Qty Per Inch (tpi):
0 single group
hread Size:
.250 inches single group
/inding Operating Current:
.0 amperes ac single component 2nd secondary
/inding Operating Voltage:
.00 ac volts single component 1st secondary
hread Series Designator:
Inc single group
erminal Type And Quantity:
solder stud
helf Life:
/a
nit Of Measure:

## NSN 5950-00-403-3975

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

