

View Online at <https://aerobasegroup.com/nsn/5950-00-403-4034>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.265 inches single mounting facility single center group

Mounting Slot Width:

0.160 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.880 inches

Body Width:

1.380 inches

Body Height:

2.380 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

200.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

20.70 ac volts single component single secondary

Special Features:

One neutral terminal common to three secondar windings

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0