# NSN 5950-00-403-7413

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-403-7413

#### **Reliability Indicator:**

Not establishednot established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

#### **Overall Height:**

4.000 inches 4.000 inches

## Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 400.0 hertz single component400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

#### **Body Length:**

3.120 inches 3.120 inches

#### **Body Width:**

2.810 inches 2.810 inches

#### **Body Height:**

3.620 inches 3.620 inches

## Inclosure Type:

Hermetically sealed with oilhermetically sealed with oil

#### **Mounting Facility Quantity:**

4 single group4 single group

#### **Mounting Method:**

Threaded stud single groupthreaded stud single group

# **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

# Thready Qty Per Inch (tpi):

32 single group32 single group

#### **Thread Size:**

0.164 inches single group0.164 inches single group

#### **Winding Operating Voltage:**

28.80 ac volts single component single secondary115.00 ac volts single component single primary

#### **Test Data Document:**

93024-300109 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

5 tab, solder lug

#### Shelf Life:

N/a

# NSN 5950-00-403-7413

Power Transformer - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A058b0