# NSN 5950-00-403-9712

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-403-9712

#### **Reliability Indicator:**

Not establishednot established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility single center group3.375 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.187 inches single mounting facility single center group3.187 inches single mounting facility single center group

#### Frequency Rating:

60.0 hertz single component and 60.0 hertz single component and 400.0 hertz single component400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

#### **Body Length:**

5.000 inches 5.000 inches

#### **Body Width:**

4.312 inches 4.312 inches

#### **Body Height:**

3.687 inches 3.687 inches

#### **Inclosure Type:**

Hermetically sealedhermetically sealed

# **Mounting Facility Quantity:**

4 single group4 single group

#### **Mounting Method:**

Threaded hole single groupthreaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

# Thready Qty Per Inch (tpi):

32 single group32 single group

#### **Thread Size:**

0.190 inches single group0.190 inches single group

# Winding Operating Voltage:

2.00 ac volts single component 1st secondary and 3.60 ac volts single component 1st secondary and 3.80 ac volts single component 1st secondary

#### **Special Features:**

Terminal no. 5 used in lieu of 1 for 400 hertz

#### **Test Data Document:**

37674-42498 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# **Thread Series Designator:**

Unf single group

#### **Terminal Type And Quantity:**

15 tab, solder lug

# Shelf Life:

N/a

# NSN 5950-00-403-9712

Power Transformer - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A058b0