

View Online at <https://aerobasegroup.com/nsn/5950-00-406-0286>

**Reliability Indicator:**

Not established

**Mounting Hole Diameter:**

0.156 inches single group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:**

1.312 inches

**Body Width:**

1.312 inches

**Body Height:**

1.562 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Distance Between Mounting Facility Centers:**

0.937 inches single mounting facility single center group and 0.937 inches single mounting facility single center group

**Inclosure Type:**

Partially enclosed, double shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Winding Operating Current:**

250.0 milliamperes dc single component 2nd secondary

**Winding Operating Voltage:**

60.00 ac volts single component 1st secondary

**Test Data Document:**

10001-2817045 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0