

View Online at <https://aerobasegroup.com/nsn/5950-00-406-0286>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

1.312 inches

Body Width:

1.312 inches

Body Height:

1.562 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

0.937 inches single mounting facility single center group and 0.937 inches single mounting facility single center group

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

250.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

60.00 ac volts single component 1st secondary

Test Data Document:

10001-2817045 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0