

View Online at <https://aerobasegroup.com/nsn/5950-00-406-4210>

Reliability Indicator:

Not establishednot establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 47.0 hertz single component and 47.0 hertz single component and 63.0 hertz single component63.0 hertz single component63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Body Length:

3.938 inches 3.938 inches 3.938 inches

Body Width:

3.375 inches 3.375 inches 3.375 inches

Body Height:

5.250 inches 5.250 inches 5.250 inches

Inclosure Type:

Hermetically sealedhermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 6 secondary single component6 secondary single component6 secondary single component

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

75.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

50.00 ac volts single component 2nd secondary25.00 ac volts single component 3rd secondary14.00 ac volts single component 4th secondary10.00 ac volts single component single primary and 15.00 ac volts single component single primary and 20.00 ac volts single component single primary

Special Features:

1primary winding; 6secondary windings

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Fig:

A058b0