

View Online at <https://aerobasegroup.com/nsn/5950-00-407-8283>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Overall Height:

5.338 inches

Frequency Rating:

50.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 4.563 inches and 4.688 inches

Body Width:

Between 3.875 inches and 4.000 inches

Body Height:

Between 4.750 inches and 4.938 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

3 primary single component and 8 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

8.5 amperes ac single component 2nd secondary

Winding Operating Voltage:

9.50 ac pounds per hour wet single component 1st secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

21 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0