

View Online at <https://aerobasegroup.com/nsn/5950-00-408-8515>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

1.937 inches 1.937 inches

Body Width:

1.812 inches 1.812 inches

Body Height:

2.750 inches 2.750 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

500.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

6.00 ac volts single component 2nd secondary26.00 ac volts single component 4th secondary10.80 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0