

View Online at <https://aerobasegroup.com/nsn/5950-00-410-7799>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.182 inches single mounting facility single center group and 2.182 inches single mounting facility single center group and 2.192 inches single mounting facility single center group2.192 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.995 inches single mounting facility single center group and 1.995 inches single mounting facility single center group and 2.005 inches single mounting facility single center group2.005 inches single mounting facility single center group

**Frequency Rating:**

47.5 hertz single component and 47.5 hertz single component and 420.0 hertz single component420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to secondary center tap single componentinternal shield grounded to secondary center tap single component

**Body Length:**

Between 2.672 inches and 2.672 inches and 2.704 inches 2.704 inches

**Body Width:**

Between 2.484 inches and 2.484 inches and 2.516 inches 2.516 inches

**Body Height:**

2.250 inches 2.250 inches

**Maximum Operating Temp:**

130.0 degrees celsius130.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

1.0 amperes dc single component single secondary

**Winding Operating Voltage:**

28.00 ac volts single component single secondary115.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0