NSN 5950-00-411-6192

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-411-6192

| view Offiline at https://acrobasegroup.com/nsi//3330-00-411-0132 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.530 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.250 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.193 inches single group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 200.00 millihenries single component single winding |
| Frequency Rating: |
| 800.0 hertz single component |
| Body Length: |
| 3.380 inches |
| Body Width: |
| 3.380 inches |
| Body Height: |
| 2.810 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Operating Current: |
| 2.0 amperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 4.000 single component single winding |
| Terminal Type And Quantity: |
| 2 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-411-6192

Reactor - Page 2 of 2



Fiig:

A058b0