

View Online at <https://aerobasegroup.com/nsn/5950-00-412-2329>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility single center group

Overall Height:

3.000 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.000 inches

Body Width:

2.250 inches

Maximum Operating Temp:

70.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

500.0 milliamperes ac single component 4th secondary

Winding Power Rating:

176.0 volts-amperes single component single primary

Winding Operating Voltage:

28.00 ac volts single component 3rd secondary 115.00 ac volts single component single primary 12.00 ac volts single component 4th secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0