## NSN 5950-00-412-2329

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-412-2329

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.625 inches single mounting facility single center group

### **Overall Height:**

3.000 inches

### **Frequency Rating:**

400.0 hertz single component

### Input-output Phase Relationship:

Three phase to three phase single component

### **Transformer Winding Connection Type:**

Delta-delta

### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

### **Body Length:**

4.000 inches

### **Body Width:**

2.250 inches

### **Maximum Operating Temp:**

70.0 degrees celsius

### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded hole single group

### **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

### **Thread Size:**

0.164 inches single group

### **Winding Operating Current:**

500.0 milliamperes ac single component 4th secondary

### **Winding Power Rating:**

176.0 volts-amperes single component single primary

### **Winding Operating Voltage:**

28.00 ac volts single component 3rd secondary115.00 ac volts single component single primary12.00 ac volts single component 4th secondary

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

15 tab, solder lug

# NSN 5950-00-412-2329

Power Transformer - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0