

View Online at <https://aerobasegroup.com/nsn/5950-00-412-2331>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.400 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.130 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Transformer Winding Connection Type:

Taylor

Maximum Transformer Power Rating:

336.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

5.400 inches

Body Width:

3.130 inches

Body Height:

3.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

290.0 milliamperes ac single component single secondary

Winding Operating Voltage:

22.20 ac volts single component single secondary 115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0